



FLEXi 15 System

15" ACTIVE COMPACT PA SYSTEM

-  **Combo Pack**
-  **Poliurea Coating**
-  **Rotatable Horn**
-  **Plywood Enclosure**
-  **Dedicated Presets**
-  **Built-in Amplifier**

The FLEXi15 is a 2000W active 2.1 compact PA system with an integrated DSP processing engine that forms a precisely matched, compact system with professional acoustic properties required by DJs and musicians for both portable use or permanent installation. The 15 inch reflex loaded subwoofer provides powerful accurate bass sound while the satellites with 8 inch mid drivers and 1 inch HF drivers are responsible for natural sounding mids and crystal-clear highs.

<p>Product Type Flexible Active PA System - 1 x 15" + 2 x 8"</p>	<p>Frequency Response (-6dB) 40Hz - 19kHz</p>	<p>Nominal Coverage (-6dB) 50-100° H x 55° V (User Rotatable)</p>
<p>Amplifier Technology Class D with DSP</p>	<p>Amplifier Power RMS: 1000W PGM: 2000W</p>	<p>DSP Technology 24bit 48kHz DSP</p>
<p>DSP Presets Flat Indoor, Flat Outdoor, Music, DJ, Vocal</p>	<p>Control Type Parameters Controlled on the Subwoofer Panel</p>	<p>FR Maximum SPL (calculated) 121dB</p>
<p>SW Maximum SPL (calculated) 127dB</p>	<p>Subwoofer Driver 15" Woofer 3" Voice Coil</p>	<p>Low Frequency Driver 8" Woofer 1.5" Voice Coil</p>
<p>High Frequency Driver 1.4" Driver 1.35" Voice Coil</p>	<p>Audio Signal Inputs Mono / Stereo Analog Audio</p>	<p>Input Connectors 2 x XLR / TRS Combo</p>
<p>Audio Signal Outputs Mono / Stereo Analog Audio</p>	<p>Output Connectors 2 x XLR</p>	<p>Speakers Output Connectors 2 x NL4 (1+/1-)</p>
<p>Protections Overload and Overcurrent</p>	<p>Operating Temperature Range 0°C - 45°C (32°F - 113°F)</p>	<p>Cooling Type Speed Controlled Fan</p>
<p>Power Supply Switching Mode Power Supply (SMPS)</p>	<p>Power Input AC 110V - 120V AC 220V - 240V 50Hz/60Hz</p>	<p>Mains Connector Standard IEC socket</p>
<p>Power Consumption 280W (1/8 Max. Power)</p>	<p>Special Features Subwoofer Phase (0° / 180°) Input Type (Mono / Stereo) Main Level Adjust. Subwoofer Level Adjust.</p>	<p>Fittings 35mm Pole Mount Socket</p>
<p>Handles Subwoofer: One on Each Side Satellite: One on Top</p>	<p>Grille Powder Coated Steel Grille with Acoustical Foam</p>	<p>Construction 12mm and 15mm Multi-Laminate Plywood</p>
<p>Finish Poliurea Coating</p>	<p>Dimensions (WxHxD) Subwoofer: 440 x 655 x 583mm (17.3 x 25.8 x 23 in) Satellite: 250 x 440 x 238mm (9.8 x 17.3 x 9.4 in)</p>	<p>Accessories Speaker Cables and Subwoofer Wheels are included</p>